



Material Safety Data Sheet

Infosafe No. LPT9M Issue Date : April 2007 ISSUED by PARCHEMC

Product Name : FOSROC CONBEXTRA EP120 HARDENER

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name FOSROC CONBEXTRA EP120 HARDENER
Company Name Parchem Construction Products Pty Ltd (ABN 80 069 961 968)
Address 7 Lucca Road Wyong
NSW 2259 Australia
Emergency Tel. 1800 638 556
Telephone/Fax Number Tel: 02 4350 5000
Fax: 02 4351 2024
Recommended Use Hardener component of epoxy grout
Other Information This MSDS summaries at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Products Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.
If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

www.parchem.com.au

2. HAZARDS IDENTIFICATION

Hazard Classification HAZARDOUS SUBSTANCE.
DANGEROUS GOODS.
Hazard classification according to the criteria of NOHSC.
Dangerous goods classification according to the Australia Dangerous Goods Code.

Risk Phrase(s) R21/22 Harmful in contact with skin and if swallowed.
R34 Causes burns.
R43 May cause sensitization by skin contact.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrase(s) S23 Do not breathe gas/fumes/vapour/spray
S24/25 Avoid contact with skin and eyes.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S61 Avoid release to the environment. Refer to special instructions/safety data sheet.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	TOFA, Reaction Products With TEPA	68953-36-6	60-100 %
	Tetraethylenepentamine	112-57-2	10-15 %
	Isophorone diamine	2855-13-2	10-15 %

4. FIRST AID MEASURES

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion Never give anything by mouth if victim is semi-conscious or unconscious. Do NOT induce vomiting. Immediately wash out mouth with water. Seek immediate medical attention.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Ensure contaminated clothing is washed before re-use or discard. Seek immediate medical attention.

Eye If contact with the eye(s) occur, wash with running water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. Seek immediate medical attention.



Material Safety Data Sheet

Page: 2 of 5

Infosafe No. LPT9M Issue Date : April 2007 ISSUED by PARCHEMC

Product Name : FOSROC CONBEXTRA EP120 HARDENER

First Aid Facilities An eye wash fountain, safety shower and a general washing facility should be available adjacent to the work area.

Advice to Doctor Treat symptomatically.

Other Information For advice, contact a Poisons Information Centre (Phone eg Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media Use carbon dioxide, dry chemical, foam or water mist.

Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide, carbon dioxide, oxides of nitrogen and ammonia.

Specific Hazards Combustible liquid. This product will burn if exposed to fire.

Hazchem Code 3X

Precautions in connection with Fire Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures Remove all sources of ignition. Increase ventilation. Wear appropriate breathing apparatus and full protective clothing to minimise skin and eye exposure. Do not dilute material but contain. Place inert, non-combustible absorbent material onto the spillage. Collect the material using clean non-sparking tools and place into a suitable labelled container for subsequent disposal. If this material enter the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. HANDLING AND STORAGE

Precautions for Safe Handling Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. Wear appropriate protection. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for Safe Storage Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. Provide a catch-tank in a bunded area. For information on the design of the storeroom, reference should be made to AS 3780-1994 The storage and handling of corrosive substances and AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards No exposure standards have been established for this material by the National Occupational Health And Safety Commission (NOHSC). However, as with all chemicals, exposure should be kept to the lowest possible levels.

Biological Limit Values No biological limit allocated.

Engineering Controls Provide sufficient ventilation. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required. Refer to AS 3780-1994 The storage and handling of corrosive substances and AS1940 - The storage and handling of flammable and combustible liquids and AS2430 - Explosive gas atmospheres for further information concerning ventilation requirements.



Material Safety Data Sheet

Page: 3 of 5

Infosafe No. LPT9M Issue Date : April 2007 ISSUED by PARCHEMC

Product Name : FOSROC CONBEXTRA EP120 HARDENER

Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependent upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.
Eye Protection	Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Medium viscosity light brown liquid
Odour	Amine like odour
Melting Point	Not available
Boiling Point	>200°C
Solubility in Water	Slight soluble
Specific Gravity	0.95 @23°C
pH Value	Not available
Vapour Pressure	Not available
Vapour Density (Air=1)	Not available
Flash Point	>100°C (Isophoronediamine)
Flammability	Classified as a Class C1 (COMBUSTIBLE LIQUID) for the purposes of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well ventilated area away from naked flames, sparks and other sources of ignition.
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions.
Conditions to Avoid	Heat, flames and other ignition sources.
Incompatible Materials	Strong oxidising agents, strong acids and metals.
Hazardous Decomposition Products	Thermal decomposition and combustion produce noxious fumes containing oxides of carbon, oxides of nitrogen, ammonia and hydrogen cyanide.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION



Material Safety Data Sheet

Page: 4 of 5

Infosafe No. LPT9M Issue Date : April 2007 ISSUED by PARCHEMC

Product Name : FOSROC CONBEXTRA EP120 HARDENER

Toxicology Information	For Isophoronediamine: LD50(oral, rat): 1030 mg/kg LD50(dermal, rabbit): 2000 mg/kg
Inhalation	Inhalation of mists or vapours will result in respiratory irritation and possible harmful corrosive effects including lesions of the nasal septum, pulmonary edema, pneumonitis and emphysema.
Ingestion	Harmful if swallowed. Ingestion of this product may cause nausea, vomiting, abdominal pain and chemical burns to the mouth, throat and stomach.
Skin	Harmful in contact with skin. Skin contact will cause redness, itching, irritation, severe pain and chemical burns with resultant tissue destruction. This product may cause sensitisation in some individuals.
Eye	Eye contact will cause stinging, blurring, tearing, severe pain and possible permanent corneal damage.
Chronic Effects	Prolonged or repeated skin contact may cause defatting leading to skin burns and skin sensitisation.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Persistence / Degradability	Not available
Mobility	Not available
Environ. Protection	Prevent this material entering waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	Dispose of waste according to federal, EPA and state regulations.
--------------------------------	---

14. TRANSPORT INFORMATION

Transport Information	This material is classified as a Class 8 (Corrosive) Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. Dangerous goods of Class 8 (Corrosive) are incompatible in a placard load with any of the following: - Class 1, Explosive - Class 4.3, Dangerous When Wet Substance - Class 5.1, Oxidising Agent - Class 5.2, Organic Peroxide - Class 6, Toxic and Infectious Substances, if the Class 6 dangerous goods are cyanides and the Class 8 dangerous goods are acids - Class 7, Radioactive Substance and are incompatible with food and food packaging in any quantity.
U.N. Number	2735
Proper Shipping Name	AMINES, LIQUID, CORROSIVE, N.O.S. - (CONTAINS ISOPHORONE DIAMINE AND TETRAETHYLENEPENTAMINE)
DG Class	8
Hazchem Code	3X
Packaging Method	3.8.8
Packing Group	III
EPG Number	8A1
IERG Number	36

15. REGULATORY INFORMATION

Poisons Schedule	S5
Hazard Category	Harmful, Corrosive

16. OTHER INFORMATION

Date of preparation or last revision of MSDS	MSDS Reviewed: April 2007 MSDS Superseded: September 2004
---	--



Material Safety Data Sheet

Page: 5 of 5

Infosafe No.	LPT9M	Issue Date : April 2007	ISSUED by PARCHEMC
--------------	-------	-------------------------	--------------------

Product Name : **FOSROC CONBEXTRA EP120 HARDENER**

Contact Person/Point Technical Support: 1800 812 864

...End Of MSDS...