

## MATERIAL SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: **MASTERFLOW 648CP+, PART A**  
Other name: Ceilcote 648CP+ (A)  
Product code: 2010201009004\_, 2010201009006\_, 2010201009008\_  
Recommended use: Part A of a three component, high strength flowable grout for use at elevated service temperatures.

Company: BASF Construction Chemicals Australia Pty Ltd.  
ABN: 46 000 450 288  
Address: 11 Stanton Road,  
Seven Hills, NSW, 2147, Australia  
Telephone number: +61 2 8811 4200  
Facsimile: +61 2 8811 3299

Company: BASF Construction Chemicals New Zealand Ltd.  
Address: 45 William Pickering Drive,  
Albany, Auckland,  
New Zealand  
Telephone number: +64 9 414 7233  
Facsimile: +64 9 414 7244

Emergency telephone number: 0417 658 263, 0438 988 699

### 2. HAZARDS IDENTIFICATION

Hazard classification: Hazardous according to criteria of NOHSC  
Risk phrase(s): R 36/38 - Irritating to eyes and skin.  
R 43 - May cause sensitisation by skin contact.  
Safety phrase(s): S 28 - After contact with skin, wash immediately with plenty of soap and water.  
S 37/39 - Wear suitable protective clothing, gloves and eye/face protection.  
S 51 - Use only in well ventilated areas.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

#### INGREDIENTS

Chemical Name	CAS Number	Proportion
Bisphenol A epoxy resin	25068-38-6	> 60%
Alkyl glycidyl ether	68609-97-2	10 -< 30%
Non-hazardous ingredients		to 100%

### 4. FIRST AID MEASURES

Ingestion: Do NOT induce vomiting. Wash mouth with water and seek medical attention.  
Eyes: While holding eyes open, gently flood with plenty of fresh water for 15 minutes. If irritation persists or recurs seek medical attention. Skilled personnel should only undertake removal of contact lenses after an eye injury.

## MATERIAL SAFETY DATA SHEET

Skin: Flush contacted area thoroughly with soap and plenty of water. Seek medical attention in event of irritation.

Inhalation: Remove to fresh air. If breathing is difficult give oxygen.

First aid facilities: Ensure availability of clean water for eye/skin wash.

Advice to doctor: Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Foam, CO<sub>2</sub> and Dry Chemical.

Hazards from combustion products: Oxides of carbon and other possibly toxic fumes from fire.

Precautions and equipment for fire fighters: Full protective clothing as per personal protection, section 8.

### 6. ACCIDENTAL RELEASE MEASURES

Methods for clean up / collecting: Small or major spills should be absorbed with dry, inert filler (soil or sand) which then can be shovelled into appropriately labelled drums for disposal.

Environmental precautions: Do not discharge into sewers unless connected to a wastewater treatment plant.

### 7. HANDLING AND STORAGE

#### Conditions for safe storage

Location: Store in a cool, dry area.

Temperature conditions: 5 to 35°C

Protection from weather: Store undercover and away from moisture and frost.

Storage incompatibilities: Strong oxidising agents, acids and alkalis.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards: Not available

Engineering controls: Ventilation is recommended under normal use conditions. State regulations on speed and direction of airflow away from operators must be observed. Keep containers closed when not in use.

Respiratory protection: Type A1 if ventilation is inadequate.

Glove type (AS2161): Long PVC or nitrile rubber gauntlets

Eye protection: Chemical worker's goggles.

Clothing: Overalls

Other: Use barrier creams to protect skin from contact with the material. Always wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colourless to pale yellow, low viscosity

Boiling point (°C): > 200

Melting point (°C): Not available

BASF Material Safety Data Sheet according to NOHSC: 2011 (2003)

## MATERIAL SAFETY DATA SHEET

Vapour pressure @ 25°(kPa): < 0.01  
Specific gravity: ca. 1.1  
Flash point (°C): > 100  
Flammability limits (%): UEL – Not applicable  
LEL – Not applicable  
Solubility in water: Insoluble  
pH: > 7

### 10. STABILITY AND REACTIVITY

Hazard of use/storage: Stable under normal storage and application temperature.  
Materials to avoid: Strong oxidising agents, acids and alkalis.  
Hazardous decomposition products: Oxides of carbon and other possibly toxic fumes from fire.

### 11. TOXICOLOGICAL INFORMATION

#### Acute

Ingestion: Only slightly toxic. [Oral, rat LD<sub>50</sub>: > 5000mg/kg]  
Eye: May cause eye irritation and redness.  
Skin: Mild skin irritation and redness from prolonged contact.  
Inhalation: May cause irritation to nose and mucous membrane.

Chronic: Susceptible individuals may develop allergic reactions such as dermatitis or asthma-like symptoms on a single significant skin exposure or may become sensitised to the material on repeated contact. Hence it is imperative that all forms of exposure be kept to an absolute minimum.

### 12. ECOLOGICAL INFORMATION

Ecology: Do not discharge into sewers unless connected to a wastewater treatment plant.

### 13. DISPOSAL CONSIDERATIONS

#### Disposal Methods

State/Territory authority: Observe all Federal, State and Local regulations  
Dispose – Secure landfill: Yes.  
Dispose – High temp incinerator: Yes.  
Precautions for clean up crew: Full protective clothing as per personal protection, section 8.

### 14. TRANSPORT INFORMATION

UN number: None allocated  
Dangerous goods class: None allocated  
Subsidiary risk: None allocated  
EPG card: None allocated  
Shipping name: None allocated  
Packing group: None allocated  
Poisons schedule: 5

## MATERIAL SAFETY DATA SHEET

Hazchem code: None allocated

### 15. REGULATORY INFORMATION

Risk phrase(s):	R 36/38	- Irritating to eyes and skin.
	R 43	- May cause sensitisation by skin contact.
Safety phrase(s):	S 28	- After contact with skin, wash immediately with plenty of soap and water.
	S 37/39	- Wear suitable protective clothing, gloves and eye/face protection.
	S 51	- Use only in well ventilated areas.

### 16. OTHER INFORMATION

Reason for Issue: Change of company name.

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request. All information contained in this MSDS is as accurate and up-to-date as possible. No warranty expressed or implied is made as to its accuracy, reliability or completeness.